

Cool Top Trail 20/24/28/34/35

Roof top air-conditioning systems



For an ideal climate in your RV

The Cool Top Trail air conditioners are suitable for use in parked motorhomes and caravans of up to 10 m length. With their generously sized heat exchangers they have a high efciency and high performance. Their reliability and high cooling capacity has already been proven in very hot Australian summers with up to 50 °C outside temperatures. The units come with heat pump function as a standard which is also very powerful, working in cold outside temperatures of as low as -5 °C.

High performance at low noise Very low noise levels allow you to rest and relax inside the vehicle and not disturb your neighbors in the RV campsite. The use of high-quality components ensures a long lifetime with a minimum expenditure on maintenance.

Product highlights

- Powerful units with high cooling and heating capacity
- Robust, lightweight and low noise
- Wide operating range from -5 to 50 °C
- Low profile and compact design
- Easy installation

Made from UV stabilized polypropylene, the housing of the units is robust but still lightweight. The units can be operated with an easy to handle remote control which allows the user to access all air conditioner functions from the comfort of the dining area, seat or bed. Besides cooling and heating the units include various extra features such as dehumidication, timer and sleep function.

Technical specications:

Cool Top Trail	20	24	28	34	35
Cooling capacity (W)	2,000	2,400	2,800	3,400	3,500
Heating capacity (W)	2,000	2,400	2,600	3,000	3,500
Nominal voltage/ frequency (V) / (Hz)	230~/50				
Rated current (cooling mode)	3	4.2	5,0	5.8	5,6
Rated current (heating mode)	2.6	3.8	4,8	5.4	5,2
Operating temperature range (°C)	-5 to 50				
Roof thickness (mm)	25 – 85		25 - 70	25 – 70	25 - 70
Roof cut-out (mm)	400 x 400 (360 x 360 with optional adaptor frame)				
Dimensions outdoor unit (mm)	1,002 x 566 x 215		855 x 657 x 215	1,122 x 850 x 223	998 x 680 x 340
Dimensions inner unit (mm)	557 x 536 x 43		575 x 556 x 49	575 x 556 x 49	557 x 536 x 43
Weight total (kg)	30.8	31.8	35,5	48	38,3

